




Technical Datasheet

Product Code: PA135015BKSR

Description: C13 IEC Locking Appliance Outlet - Right Locking Orientation - Black



General Information

Rating	10A Max / 250V~ (Europe) 15A Max / 250V~ (cUL)
Materials	Face & Back Cover: Polyamide 66 (PA66) - To RAL Colour 9004 (Signal Black) Gloss Finish Contacts: Tin Plated Copper Alloy (CuSn5 PB102 1/2 Hard Phosphor Bronze) Push Button: Polycarbonate - To RAL Colour 3020 (Traffic Red) Spring: Steel (Zinc Plated) Locking Blade: Spring Steel Zinc Plated Button: Polycarbonate (RAL 3020 Traffic Light Red) -20 to +70
Panel Thickness	1.5mm
Aperture Cutout	25-25.2mm (H) x 34.1-34.3mm (W)
Receptacle Size	6.3mm x 0.8mm
Insulation Resistance	100MΩ (500V DC, 1 Min)
Dielectric Strength	2KV (50Hz 1Min) to accessible surfaces
Temperature Rating	-20°C To + 70°C
Lock Retention	> 100N
Features	Fits any standard C14 connector Anti-Vibrate Integral plug retention feature Easy push button to release

Standards	IEC /BS EN 60320-1: 2021 IEC /BS EN 60320-3 UL 60320-1 UL 60320-3 CSA C22.2 60320-1-19 CSA C22.2 60320-3
------------------	---

